



Solar, Safety and Security Window Films

Care & Maintenance of Window Film

I. Commercial applications: Interior window films

1 Appearance

It is unlikely, but possible, to see a “haziness” or “fogginess” in the film immediately after installation. This is the result of a minute amount of moisture left under the film after installation. This is normal and should not be a matter of concern. This will disappear in a few days, depending on weather conditions.

2 Cleaning window film

Window film is less porous than glass, will not accumulate dirt as quickly as glass and is easier to clean. Cleaning of film is required less frequently than the cleaning of glass. A simple solution of a mild dishwashing detergent and water will suffice for most pollutants. Commercial glass cleaning products are acceptable but not required. Use only soft cloths or paper towels to wipe off cleaning solution. If janitorial service is used for window cleaning, please make certain they receive a copy of this bulletin.

3 Window film maintenance

Although there is no maintenance required for the film to perform as expected, there are some steps that can be taken to keep the film looking new for many years. On interior films, occasionally use a silicone polish to provide a lustrous surface to the film. This will also prevent most instances of unexpected scratching or burnishing which could happen to the film. Some suggested silicone products are:

- Plexus Plastic Cleaner
- Solar Majik

4 Tape removal from film

If adhesive tape is ever applied to the film and needs to be removed, simply peel it off as though it is on the glass. If there is residual adhesive left behind, this can be removed with a soft cloth and mineral spirits or alcohol. If the adhesive is unusually stubborn, then methyl ethyl ketone (MEK) or acetone may be used with a soft cloth.

II. Commercial applications: Exterior window films

5 Cleaning window film

In many cases, exterior window film is cleaned by professional window cleaning companies. Never clean filmed windows with bristle brushes or abrasive cloths. This is not necessary and will damage the film, possibly voiding the warranty. A soft cloth with a mild solution of detergent and water is all that is needed. It is permissible to squeegee off the rinse water. Please make certain that any commercial window cleaning services receive a copy of this bulletin.

www.solargard.com

Saint-Gobain Solar Gard
European Regional Headquarters
Karweg 18, 9870 Zulte, Belgium
E: info.emea@solargard.com
T: +32 9 240 95 66

PDF0250SG20MAINCOMINT 11/17
© Copyright 2017, Saint-Gobain Performance Plastics and/or its affiliates
All Rights Reserved • www.solargard.com

 Please recycle